



PRODUCT SPECIFICATION SHEET

Defoamer

Item No. FCCCDF1

Description:

Concentrated and Fast-Acting - This highly concentrated product quickly eliminates foam in the equipment recovery tank, extending the time of use prior to emptying of tank. Normal use prevents moisture from entering vacuum motor, extending motors life. Use in extractors, scrubbers, wet vacuums - anywhere that excessive foam is a problem.

Features & Benefits:

- Fast acting - Breaks foam on contact
- Saves time - Eliminates downtime and wasted effort in dumping recovery tanks.
- Versatile - Has many uses and can be used anywhere foaming is a problem.

Directions:

Recommended for use in recovery tanks of extraction machines or automatic scrubbers where foaming might be a problem. Shake or mix container well before using.

Extractors or Automatic Scrubbers: Initially place 1 oz. of defoamer per gallon capacity of the pick up tank (8 mL/L) 1:128. If carpet is full of shampoo from previous cleanings, more defoamer may be needed.

Sewage Systems or Water Plants: Add defoamer, wait a few minutes for it to disperse, continue until suds subside.

Ideal for use in:

- Auto scrubber
- Extractors
- Sewage systems or water plants



Specifications-

Color	Milky white
Scent	Characteristic
pH	7.0 to 8.0
Flash Point	None

Ingredients:

Water (7732-18-5); Polydimethylsiloxane (N/A); Acrylic Polymer (N/A); DMDM Hydantoin (6440-58-0); Sodium Hydroxide (1310-73-2).

Storage & Shelf Life:

Keep from freezing, 2 year warranty

Registrations & Certifications -