T663M TREADMILL

Make rehabilitative workouts more effective with the T663M Treadmill. With a durable 3.2 HP DC motor and a maintenance-minimizing ECO-GLIDE™ auto lubrication system, it is a standout in value and technology. Extended medical handrails, reverse speed capability and microamp leakage filter make this the perfect treadmill for rehabilitation settings. What's more, the MyFlex+ omni-directional cushioning provides unmatched support and comfort, minimizing the strain on joints and muscles with each stride. With a speed range from -3.0 to 10 mph, a starting speed of 0.1 mph, and a variety of preset workouts, it offers a great fitness experience at an exceptional price.



KEY FEATURES

- Bi-directional belt motion for retro walking and gait observations
- Isolation components meet UL requirements for current leakage in medical settings
- Full length medical side rails with pediatric lower sections for better patient stability

TECHNICAL DETAILS

Unit Weight	367.4 lbs / 167 kg
Dimensions (LxWxH)	83.3 x 38.6 x 58.3 in / 211.4 x 97.9 x 147.9 cm
Running Area (LxW)	61 x 22 in / 155 x 55.9 cm
Speed Range	Reverse: 0.1–3.0 mph / Forward: 0.1–10 mph
Incline Range	0–15%
Drive Motor	3.2 HP DC
Power Requirements	15A / 120v / 60Hz - Dedicated Circuit 220V / 50HZ
Plug Requirements	NEMA / 5-15P* Contact your sales rep for specific requirements
Max User Weight	400 lbs / 180 kg
Step Up Height	8 in / 20.4 cm
Micro Amp Leakage Components	Medical Grade ≤ 300µA, Green Dot Power Cord
Readouts	Calories, Speed, Time, Distance, Cal/HR, METs, Pace, Incline, Heart Rate, Weight Loss Zone, Cardio Zone, ActivZone
Workout Programs	Quick Start, Manual, Random (x 10,000), Interval (x3), Glute (x2), Hill (x3), 5K, 10K, Fat Burn, HRC (x3), Fitness Test (Bruce, Gerkin)
Features	CSAFE port Medical handrails 0.1 SafeStart™ speed (forward & reverse) Contact and telemetry heart rate 4-Ply 61 x 22 in. belt USB port for device charging ECO-GLIDE™ auto lubrication system Center handle bar with contact heart rate Emergency stop MyFlex+ omni-directional cushioning system Manufactured to meet EN ISO 20957 / ASTM F2276 standards
Optional Features	Wired controller remote 3-speed fan

WARRANTY*

Type	Light Commercial
Frame	Lifetime**
MyFlex+	Lifetime**
Motor	Lifetime**
Parts	5 Years
Wear Items	5 Years
Labor	3 Years
High Wear Items	90 days, no labor

SPECIAL FEATURES



Forward and reverse speed function (-3–10 mph)

CONSOLE



White LED Console

OPTIONAL FEATURES



Wired Controller Remote

 ©2024 SPORTSART. ALL RIGHTS RESERVED